





- ≡ 35,000 hour lifetime achievable depending on room temperature
- ≡ Works across a wide input voltage range of 85V-265V
- ≡ IP65 certified to be waterproof
- ≡ Uses powerful, multi-chip design LED
- ≡ High heat conductivity, low luminous decay, noiseless operation and no ghosting effect
- ≡ Electricity savings of 25-50% compared with HPS (high pressure sodium) lights and CFL light bulbs
- ≡ Multiple white colours available in the 2700K-6500K range



Part No	LFH030200A-10	LFH040200A-10	LFH050200A-10	LFH060200A-10	LFH070200A-10	LFH080200A-10	LFH100200A-10	LFH120200A-10	LFH140200A-10
<b>Wattage (W)</b>	30	40	50	60	70	80	100	120	140
<b>Voltage Range (V)</b>	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24
<b>Lumens (lm)</b>	2400	3200	4000	4800	5600	6400	8000	9600	11200
<b>Luminous Efficiency (lm/W)</b>	80	80	80	80	80	80	80	80	80
<b>Color</b>	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW
<b>Beam Angle (°)</b>	80	80	80	80	80	80	80	80	80
<b>Cover</b>	Clear	Clear	Clear	Clear	Clear	Clear	Clear	Clear	Clear
<b>LED Q'ty</b>	1	1	1	1	1	2	2	2	2
<b>Life Time (Hrs)</b>	35000	35000	35000	35000	35000	35000	35000	35000	35000
<b>Dimensions (mm) AxBxC</b>	393x285x93	393x285x93	393x285x93	393x285x93	393x285x93	593x285x93	593x285x93	593x285x93	593x285x93
<b>Certificates</b>	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS

