





- ≡ 35,000 hour lifetime achievable depending on room temperature
- ≡ Works across a wide input voltage range of 85V-265V
- ≡ IP65 certified to be waterproof
- ≡ Uses a single, powerful, multi-chip design LED
- ≡ High heat conductivity, low luminous decay, noiseless operation and no ghosting effect
- ≡ Electricity savings of 25-50% compared with HPS (high pressure sodium) lights and CFL light bulbs
- ≡ Multiple white colours available in the 2700K-6500K range



Part No	LFL010200A-10	LFL020200A-10	LFL025200A-10	LFL030200A-10	LFL040200A-10
<b>Wattage (W)</b>	10	20	25	30	40
<b>Voltage Range (V)</b>	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24
<b>Lumens (lm)</b>	800	1600	2000	2400	3200
<b>Luminous Efficiency (lm/W)</b>	80	80	80	80	80
<b>Color</b>	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW
<b>Beam Angle (°)</b>	80	80	80	80	80
<b>Cover</b>	Frosted	Frosted	Frosted	Frosted	Frosted
<b>LED Q'ty</b>	1	1	1	1	1
<b>Life Time (Hrs)</b>	35000	35000	35000	35000	35000
<b>Dimensions (mm) AxBxC</b>	262x185x230	262x185x230	262x185x230	262x185x230	262x185x230
<b>Certificates</b>	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS

