





- ≡ 35,000 hour lifetime achievable depending on room temperature
- ≡ Works across a wide input voltage range of 85V-265V
- ≡ IP65 certified to be waterproof
- ≡ Uses powerful, multi-chip design LED from Bridgelux USA as the light source
- ≡ High heat conductivity, low luminous decay, noiseless operation and no ghosting effect
- ≡ Electricity savings of 25-50% compared with HPS (high pressure sodium) lights and CFL light bulbs
- ≡ Multiple white colours available in the 2700K-7000K range



Part No LPH030200A-10 LPH040200A-10 LPH050200A-10 LPH060200A-10 LPH070200A-10 LPH080200A-10 LPH100200A-10 LPH120200A-10 LPH140200A-10

Part No	LPH030200A-10	LPH040200A-10	LPH050200A-10	LPH060200A-10	LPH070200A-10	LPH080200A-10	LPH100200A-10	LPH120200A-10	LPH140200A-10
Wattage (W)	30	40	50	60	70	80	100	120	140
Voltage Range (V)	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24
Lumens (lm)	2400	3200	4000	4800	5600	6400	8000	9600	11200
Luminous Efficiency (lm/W)	80	80	80	80	80	80	80	80	80
Color	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW
Beam Angle (°)	40	40	40	40	40	40	40	40	40
Cover	Clear	Clear	Clear	Clear	Clear	Clear	Clear	Clear	Clear
LED Q'ty	1	1	1	1	1	2	2	2	2
Life Time (Hrs)	35000	35000	35000	35000	35000	35000	35000	35000	35000
Dimensions (mm) AxBxC	393x285x93	393x285x93	393x285x93	393x285x93	393x285x93	593x285x93	593x285x93	593x285x93	593x285x93
Certificates	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS

