





- ≡ 35,000 hour lifetime achievable depending on room temperature
- ≡ Works across a wide input voltage range of 85V-265V
- ≡ IP65 certified to be waterproof
- ≡ Uses powerful, multi-chip design LED from Bridgelux USA as the light source
- ≡ High heat conductivity, low luminous decay, noiseless operation and no ghosting effect
- ≡ Electricity savings of 25-50% compared with HPS (high pressure sodium) lights and CFL light bulbs
- ≡ Multiple white colours available in the 2700K-7000K range



Part No	LPL010200A-10	LPL020200A-10	LPL025200A-10	LPL030200A-10
Wattage (W)	10	20	25	30
Voltage Range (V)	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24
Lumens (lm)	800	1600	2000	2400
Luminous Efficiency (lm/W)	80	80	80	80
Color	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW
Beam Angle (°)	40	40	40	40
Cover	Frosted	Frosted	Frosted	Frosted
LED Q'ty	1	1	1	1
Life Time (Hrs)	35000	35000	35000	35000
Dimensions (mm) AxBxC	262x185x230	262x185x230	262x185x230	262x185x230
Certificates	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS

