






- ≡≡≡ 35,000 hour lifetime achievable
- ≡≡≡ Works across a wide input voltage range of 85V-265V
- ≡≡≡ IP65 certified to be dust and water proof
- ≡≡≡ Uses powerful, multi-chip design LED
- ≡≡≡ High heat conductivity, low luminous decay, noiseless operation and no ghosting effect
- ≡≡≡ Electricity savings of 25-50% compared with HPS (high pressure sodium) lights and CFL light bulbs
- ≡≡≡ Multiple white colours available in the 2700K-6500K range



Part No	LSH140200A-10	LSH160200A-10	LSH180200A-10	LSH200200A-10
Wattage (W)	140	160	180	200
Voltage Range (V)	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24
Lumens (lm)	11200	12800	14400	16000
Luminous Efficiency (lm/W)	80	80	80	80
Color	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW
Beam Angle (°)	120	120	120	120
Cover	Frosted	Frosted	Frosted	Frosted
LED Q'ty	4	4	4	4
Life Time (Hrs)	35000	35000	35000	35000
Dimensions (mm) AxBxC	910x390x190	910x390x190	910x390x190	910x390x190
Certificates	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS

