






- ≡ 35,000 hour lifetime achievable
- ≡ Works across a wide input voltage range of 85V-265V
- ≡ IP65 certified to be dust and water proof
- ≡ Uses a single, powerful, multi-chip design LED
- ≡ High heat conductivity, low luminous decay, noiseless operation and no ghosting effect
- ≡ Electricity savings of 25-50% compared with HPS (high pressure sodium) lights and CFL light bulbs
- ≡ Multiple white colours available in the 2700K-6500K range



Part No LSL030200A-10 LSL040200A-10 LSL050200A-10 LSL060200A-10 LSL070200A-10 LSL080200A-10 LSL100200A-10

Part No	LSL030200A-10	LSL040200A-10	LSL050200A-10	LSL060200A-10	LSL070200A-10	LSL080200A-10	LSL100200A-10
<b>Wattage (W)</b>	30	40	50	60	70	80	100
<b>Voltage Range (V)</b>	AC 85-265 DC 12/24	AC 85-265 DC 12/25	AC 85-265 DC 12/26	AC 85-265 DC 12/27	AC 85-265 DC 12/28	AC 85-265 DC 12/29	AC(85-265) DC(12/24)
<b>Lumens (lm)</b>	2400	3200	4000	4800	5600	6400	8000
<b>Luminous Efficiency (lm/W)</b>	80	80	80	80	80	80	80
<b>Color</b>	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW
<b>Beam Angle (°)</b>	100	100	100	100	100	100	100
<b>Cover</b>	Clear	Clear	Clear	Clear	Clear	Clear	Clear
<b>LED Q'ty</b>	1	1	1	1	1	1	1
<b>Life Time (Hrs)</b>	35000	35000	35000	35000	35000	35000	35000
<b>Dimensions (mm) AxBxC</b>	720x324x172	720x324x172	720x324x172	720x324x172	720x324x172	720x324x172	720x324x172
<b>Certificates</b>	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS

