






- ≡ 35,000 hour lifetime achievable depending on room temperature
- ≡ Works across a wide input voltage range of 85V-265V
- ≡ IP65 certified to be waterproof (submersible)
- ≡ Uses powerful, multi-chip design LED
- ≡ High heat conductivity, low luminous decay, noiseless operation and no ghosting effect
- ≡ Electricity savings of 25-50% compared with HPS (high pressure sodium) lights and CFL light bulbs
- ≡ Multiple white colours available in the 2700K-6500K range



Model	LSM060200A-10	LSM070200A-10	LSM080200A-10	LSM090200A-10	LSM100200A-10	LSM110200A-10
Wattage (W)	60	70	80	90	100	110
Voltage Range (V)	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24	AC 85-265 DC 12/24
Lumens (lm)	4800	5600	6400	7200	8000	8800
Luminous Efficiency (lm/W)	80	80	80	80	80	80
Color	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW	WW/NW/CW
Beam Angle (°)	120	120	120	120	120	120
Cover	Frosted	Frosted	Frosted	Frosted	Frosted	Frosted
LED Q'ty	2	2	2	2	2	2
Life Time (hrs)	35000	35000	35000	35000	35000	35000
Dimensions (mm) AxBxC	750x390x190	750x390x190	750x390x190	750x390x190	750x390x190	750x390x190
Certificates	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS

